

Wide belt sander

CASADEI LIBRA 10/95 TC action equipment



Compact machine with combination sanding unit. The universally applicable entry-level model.

Article number ▾

5222100A2

Brand ▾

Holzwerk CASADEI

Availability ▾

No stock available

Information:

Next availability

Expected on calendar week 24/2023

Catalog directory ▾

Woodworking machinery » Grinding machines for wood » Wide Belt Sanders » Series CASADEI LIBRA 10




Purchase ▾

Minimum 1 pc(s).

Shipping informations ▾

Packaging Metrics		Weights		Delivery		Other	
Length	1,110 mm	Gross	690 kg	Delivery	Carrier	DualUse	✘
Width	1,390 mm	Net	660 kg	Content	1 pc(s).	SCIP	n/a
Height	1,760 mm					SVHC	No

Root data ▾

Country of origin	EAN	Custom number	Quantity unit
 Italy	4036351260592	84659300	pc(s).



MADE IN ITALY

Description ▾

- Also for smaller craft shops for occasional use
- Combination sanding unit with sanding shoe for fine sanding
- Standard with diagonally grooved steel roller Ø 120 mm for calibration
- Fine adjustment of the working height
- Clear control panel on the front
- Robust tube-stiffened monobloc steel machine body, robot welded, high-mounted working units for maximum rigidity
- Motorized height adjustment of the work table with digital display
- Electronically controlled sanding belt oscillation
- Carpet feed via gear motor with two speeds
- Natural rubber feed carpet with negative profile
- Flexible steel pressure rail in front of the first unit
- Rubber rollers, in front of or behind each working unit
- Pneumatic belt tension per unit with decimal correction possibility of the grain / belt thickness
- Universally applicable for solid wood and veneer thanks to combi unit
- Entry level model for smaller companies
- Working width 950 mm

Room amenities

Combination unit for calibrating and sanding

- Slant-grooved steel roller Ø 120 mm with height fine adjustment
- Hard sanding pad with graphite pad
- Universal version for calibration and sanding of solid wood, chipboard and veneer

equipment

Option Automatic table positioning

- Adjustment of worktable height automatically via microswitch without correction of material removal
- Optionally available for Libra 10

Delivery content

- Worktable height adjustment with electronic display of the working height
- Oscillation of the sanding belts with electronic system
- Rubber-coated grooved pressure roller at inlet 1 ° position with backflow preventer
- Grooved calibration steel roller
- Switching the sanding pad on and off from the control panel
- Switching the roller on and off from the control panel
- Electronic control Fox 500 KTR
- Table extension with 2 castors in inlet and outlet


Media informations



Technical data ▼

Dimensions and weights			
Length (product) approx.	1388 mm	Width/depth (product) approx.	1545 mm
Height (product) approx.	1668 mm		
Extraction port			
Extraction port diameter	140 mm		
Electrical Data			
Feed motor output	0.33/0.55 kW	Drive motor output	7,5 kW
Supply voltage	400 V	Mains frequency	50 Hz
Height adjustment motor power	0.25 kW		
Sanding machine			
Sanding belt length	1525 mm	Sanding belt width	970 mm
Max. sanding width	950 mm		
Feed unit			
Feed speed	4.5 / 9 m/min		
Workpiece			
Min. workpiece height	4 mm	Max. workpiece height	170 mm

Options equipment ▼



Rubber roller
 ø 120 mm 85 Sh

Article number ▼
 5259072

Availability ▼
 No stock available
 Information:
 Next availability
 Unknown

Purchase ▼
 Minimum 1 pc(s).

Price informations ▼
 Ask for price





Oscillating blower sanding belt



Article number ▼
5256069

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Electronic control FOX 500 KTR




Article number ▼
5256063

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Switching the roller on and off from the control panel




Article number ▼
5256062

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Switching the sanding shoe on and off from the LIBRA 10 control panel




Article number ▼
5256060

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Semi-hard flat sanding shoe




Article number ▼
5256073

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Reinforced motor with motor 3rd unit 11 kW



Article number ▼
5256064

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼
[Ask for price](#)



Automatic table positioning with microswitch

Article number ▼
5256066

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).



Price informations ▼
[Ask for price](#)



Automatic table positioning with button


Article number ▼
5259074

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).



Price informations ▼
[Ask for price](#)



Automatic carpet centering

Article number ▼
5256067

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).



Price informations ▼
[Ask for price](#)




Table extension front and rear with 2 inlet and outlet rollers

Article number ▼
5256068

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).



Price informations ▼
[Ask for price](#)

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.